



Typ type	Abmessungen dimensions		Φ_i Prüflehre Φ_i control gauge mm	Gewicht weight g	Bestellnummer order number
	D / mm	l / mm			
S 3/200C	3 ± 0,3	200 ± 3	4	≈ 6	402 032003 026
S 4/200C	4 ± 0,3	200 ± 3	5	≈ 10	402 042003 026
S 5/200C	5 ± 0,3	200 ± 3	6	≈ 18	402 052003 026
S 6/200C	6 ± 0,3	200 ± 3	7	≈ 26	402 062003 026
S 7/200C	7 ± 0,3	200 ± 3	8	≈ 34	402 072003 026
S 8/200C	8 ± 0,3	200 ± 3	9	≈ 46	402 082003 026
S 9/200C	9 ± 0,3	200 ± 3	10	≈ 58	402 092003 026
S 10/200C	10 ± 0,35	200 ± 3	11	≈ 71	402 102003 026
S 11/200C	11 ± 0,35	200 ± 3	12	≈ 84	402 112003 026
S 12/200C	12 ± 0,35	200 ± 3	13	≈ 102	402 122003 026
S 13/200C	13 ± 0,4	200 ± 3	14	≈ 120	402 132003 026
S 14/200C	14 ± 0,4	200 ± 3	15	≈ 140	402 142003 026
S 15/200C	15 ± 0,45	200 ± 3	16	≈ 160	402 152003 026
S 16/200C	16 ± 0,5	200 ± 3	17	≈ 182	402 162003 026
S 18/200C	18 ± 0,55	200 ± 3	19	≈ 230	402 182003 026
S 19/200C	19 ± 0,55	200 ± 3	20	≈ 255	402 192003 026
S 20/200C	20 ± 0,6	200 ± 3	21	≈ 285	402 202003 026
S 22/200C	22 ± 0,65	200 ± 3	23	≈ 345	402 222003 026

Ferritmaterial K 2006 - andere Abmessungen auf Anfrage / ferrite grade K 2006 - further dimensions on request

All information given without liability. If you require further information about our products, do not hesitate to contact our representatives, or visit our homepage, www.kaschke.de.

Kaschke Components GmbH

Rudolf-Winkel-Straße 6 · 37079 Göttingen · Germany

Fon +49 (0) 5 51-50 58-6 · Fax +49 (0) 5 51-65 75 6

kaschke.de